PCI

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵:

C07C 43/11, 43/18, 43/20, C11D 1/72,
3/075, 3/20

(11) International Publication Number: WO 94/22800

(43) International Publication Date: 13 October 1994 (13.10.94)

(21) International Application Number: PCT/US94/02884
 (22) International Filing Date: 18 March 1994 (18.03.94)

(30) Priority Data: 043,108 5 April 1993 (05.04.93) US

(71) Applicant: OLIN CORPORATION [US/US]; 350 Knotter Drive, P.O. Box 586, Cheshire, CT 06410-0586 (US).

(72) Inventors: BUNCH, Henry, S.; 155 Winesap Road, Stamford, CT 06903 (US). GROOM, Theodore; 4 Laurel Lane, Northford, CT 06472 (US). GROSSER, Frank, R.; Old Litchfield Tumpike, Bethany, CT 06525 (US). SCARDERA, Michael; 81 Manor Street, Hamden, CT 06517 (US). TARGOS, Tom, S.; 725 Whitney Avenue, New Haven, CT 06511 (US). VANOVER, Arthur, R.; 70 St. Andrews Road, Bradenburg, KY 40108 (US).


(74) Agents: CARLSON, Dale, Lynn et al.; Wiggin & Dana, One Century Tower, New Haven, CT 06508-1832 (US). (81) Designated States: AU, BB, BG, BR, BY, CA, CN, CZ, FI, HU, JP, KP, KR, KZ, LK, LV, MG, MN, MW, NO, NZ, PL, RO, RU, SD, SK, UA, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: BIODEGRADABLE LOW FOAMING SURFACTANTS FOR AUTODISH APPLICATIONS

Rinse Efficacy



(57) Abstract

3

The present invention relates to a poly(oxyalkylated) alcohol composition represented by the formula: R₁O[CH₂CH(CH₃O)_k(CH₂CH₂O)_y[CH₂CH(OH)R₂]_z wherein R₁ is a linear, aliphatic hydrocarbon radical having from about 4 to about 18 carbon atoms including mixtures thereof; and R₂ is a linear, aliphatic hydrocarbon radical having from about 26 carbon atoms including mixtures thereof; x is an integer having a value from 1 to about 3; y is an integer having a value from 5 to about 30; and z is an integer having a value of from 1 to about 3. Also disclosed is an automatic dishwasher composition comprising the above-described epoxy-capped poly(oxyalkylated) alcohol and at least one component selected from the group consisting of detergent builder, bleach, anti-wear agent, and mixtures thereof. Also disclosed is a cleaning composition for cleaning hard surfaces comprising an aqueous or organic solvent and the above-described epoxy-capped poly(oxyalkylated) alcohol as a surfactant.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

		~~	#1-1 # #F1#	MR	Mauritania
AT	Austria	GB	United Kingdom		Malawi
ΑU	Australia	GE	Georgia	MW	
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	Œ	<u>ireland</u>	NZ	New Zealand
BJ	Benin	П	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgystan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic	SD	Suden
CG	Congo		of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SI	Slovenia
CI	Côte d'Ivoire	KZ	Kazakhstan	SK	Slovakia
CM	Cameroon	LI	Liechtenstein	SN	Senegal
CN	China	LK	Sri Lanka	TD	Chad
cs	Czechoslovakia	LU	Luxembourg	TG	Togo
CZ	Czech Republic	LV	Latvia	TJ	Tajikistan
DE	Germany	MC	Monaco	TT	Trinidad and Tobago
DK	Denmark	MD	Republic of Moldova	UA	Ukraine
ES	Spain	MG	Madagascar	US	United States of America
_	Finland	MIL	Mali	UZ.	Uzbekistan
FI	•	MN	Mongolia	VN	Viet Nam
FR	Prance	14114	230000 mm	***	
GA	Gabon				

15

20

25

30

-1-

BIODEGRADABLE LOW FOAMING SURFACTANTS FOR AUTODISH APPLICATIONS

The present invention relates to novel low foaming surface active agents. More particularly, the invention relates to novel low foaming surface active agents having enhanced biodegradability as well as improved performance as rinse aids in automatic dish washing and hard surface cleaner applications.

Many of the cleaning compositions heretofore recommended for use in connection with the cleaning of tableware have been subject to one or more significant disadvantages. Perhaps the paramount difficulty involved relates to the tendency of such compositions to leave undesirable spots and films on the washed tableware. As will be recognized, aesthetic considerations rather than purely functional criteria are often of overriding importance in regard to the suitability of a given cleaning composition, especially when contemplated for use in connection with the cleaning of tableware.

Further, environmental concerns have placed a premium on developing surfactants having increased biodegradability. Biodegradability is defined as that property possessed by a material enabling it to be decomposed by bacteria or other living organisms.

Ideally, surfactants utilized in the washing of tableware in automatic dishwashers will have a combination of biodegradablity characteristics and improved rinsing properties.

The prior art is replete with the disclosure of various surfactant compositions. By way of

10

15

25

illustration, U. S Patent No. 3,956,401 discloses liquid surfactants having the formula:

wherein R is a substantially linear hydrocarbon and more particularly an alkyl group having an average of from about 7 to about 10 carbon atoms; R' is a linear, alkyl hydrocarbon of from about 1 to about 4 carbon atoms; R" is a linear, alkyl hydrocarbon of from about 1 to about 4 carbon atoms; x is an integer of about 1 to about 6; y is an integer of about 4 to about 15; and z is an integer of about 4 to 25.

As another illustration, U.S. Patent No. 4,925,587 discloses hydroxyalkyl polyethylene glycol and hydroxyalkyl polypropylene glycol ether surfactants corresponding to the following general formula:

20 OH 1

 R^1 -CH-CH₂-(OCH-CH₂)_n-OR²

in which

R1 is a linear C6-C16 alkyl radical;

 R^2 is a linear or branched, saturated or unsaturated C_1 - C_{22} alkyl radical;

R₃ is hydrogen or a methyl group; and n is a number of from 0 to 30.

As yet another example, U.S. Patent 4,317,940 discloses biodegradable surfactants described as

10

15

30

being useful as agricultural emulsifiers and having the following general formula:

wherein R is a linear, alkyl hydrocarbon chain having an average of from about 6 to about 10 carbon atoms; R' is a linear, alkyl hydrocarbon of 1 to about 4 carbon atoms; R" is a linear, alkyl hydrocarbon of from about 1 to about 4 carbon atoms; x is an integer of from about 8 to about 12; y is an integer from about 19 to about 25; and z is an integer from about 2 to 7.

As still yet another illustration, U. S. Patent No. 4,827,028 discloses the production of anionic surfactants by reacting an unsaturated dicarboxylic acid such as maleic acid or fumaric acid with at least one epoxy-capped poly(oxyalkylated) alcohol having the formula (A) and (B):

wherein R is a hydrocarbon containing radical having from 1 to about 8 carbon atoms; R₁ is a hydrocarbon containing radical having from about 6 to about 18 carbon atoms; x is an integer having a value from about 6 to about 40 and y is an integer having a value from about 8 to about 50. The ratio of x:y is from about 2:8 to about 8:2; and the mole ratio of

15

20

dicarboxylic acid to epoxy-capped poly(oxylalkylated) alcohol is from about 1:1 to about 10:1. The above-described surfactants typically have high caustic solubility, which can be an important surfactant characteristic. Unfortunately, an increased emphasis on biodegradability and surfactant cleaning performance in the cleaning of tableware, particularly when utilizing detergent compositions having low phosphate concentrations, has resulted in requirements which are not completely satisfied utilizing the compositions described in the above-referenced patents.

New nonionic surfactants have been discovered which have surprisingly improved rinsing characteristics, are readily biodegradable, and are low foaming. Their use results in a significant reduction in spotting and filming of tableware, as compared to conventional surfactants, when used in automatic dishwashers.

The novel compositions are epoxy-capped poly(oxyalkylated) alcohols represented by the formula:

 $R_1O[CH_2CH(CH_3)O]_x(CH_2CH_2O)_y[CH_2CH(OH)R_2]_z$

wherein R₁ is a linear, aliphatic hydrocarbon radical having from about 4 to about 18 carbon atoms including mixtures thereof; and R₂ is a linear, aliphatic hydrocarbon radical having from about 2 to about 26 carbon atoms including mixtures thereof; x is an integer having a value from 1 to about 3; y is an integer having a value from 5 to about 30; and z is an integer having a value of from 1 to about 3. Preferred surfactant compositions include those in

15

20

25

30

35

which x is an integer having a value from about 1 to about 2, and more preferably 1. Also preferred are surfactant compositions in which y is an integer having a value from about 10 to about 25, and more preferably from about 10 to about 20. With respect to z, preferred embodiments are those in which z has a value of from 1 to about 2, and most preferably 1.

In another aspect, the present invention relates to an automatic dishwasher composition comprising the above-described epoxy-capped poly(oxyalkylated) alcohol and at least one component selected from the group consisting of detergent builder, bleach, anti-wear agent, and mixtures thereof.

In yet another aspect, the present invention relates to a cleaning composition for cleaning hard surfaces comprising an aqueous or organic solvent and the above-described epoxy-capped poly(oxyalkylated) alcohol as a surfactant.

These and other aspects will become apparent upon reading the following detailed description of the invention.

The FIGURE is a graph showing the rinse efficacy of the products of the invention, EXAMPLES 1, 2 and 3, and COMPARATIVE EXAMPLES C and D with respect to spotting of washed glassware.

Basically, the surfactant compositions of the present invention consist of four components, namely a linear alcohol, propylene oxide, ethylene oxide, and an epoxy cap. The epoxy cap and the linear alcohol serve as a hydrophobic, oil-soluble portion of the molecule. The ethylene oxide groups form the hydrophilic, water-soluble elements of the molecule.

It has been surprisingly discovered in accordance with the present invention that

15

20

25

30

35

significant improvements in biodegradability and rinsing characteristics, relativ to conventional surfactants, are provided utilizing the compositions of the present invention to clean tableware. Without wishing to be bound by any particular theory, the present inventors believe that this improvement is at least partly attributable to the ordered structure of the compositions in which limited numbers of propylene oxide groups are directly attached to the alcohol followed by addition of the ethylene oxide groups and capping using the 1,2-epoxyalkane. While maintaining this ordered structure, it is desired to also have low ratios of propylene oxide groups to ethylene oxide groups. For example, preferred ratios of propylene oxide groups to ethylene oxide groups are in the range of about 1:5 to about 1:30, and more preferably from about 1:10 to about 1:20.

Generally, these poly(oxyalkylated) alcohols may be made by condensing an aliphatic alcohol, or mixture of alcohols, having an average chain length of from 4 to about 18 carbon atoms, preferably from about 4 to about 12, and more preferably from about 6 to about 10 carbon atoms, initially with propylene oxide followed by capping this condensation product with ethylene oxide. The methods used for condensing and capping may be any of the well-known methods described in the art. Preferably, these reactions occur at elevated temperatures in the range of about 120°C to about 180°C, and more preferably at from about 140°C - 160°C. It is also preferred to carry out such reactions in the presence of an effective amount (e.g. about 0.005% to 1% by weight of the alcohol) of a suitable alkaline catalyst(s) such as hydroxides of alkali

10

15

20

25

30

35

metals or alkaline earth metals as well as alkali metal alcoholates and BF₃. The preferred catalyst is KOH.

Epoxy compounds useful for making the epoxy-capped poly(oxyalkylated) alcohols of the present invention include any 1,2-epoxyalkanes, or mixtures thereof, having a hydrocarbon chain containing an average of about 2 to about 26 carbon atoms. Preferably, the 1,2-epoxyalkane has a linear, aliphatic hydrocarbon chain containing an average of from about 8 to about 20 carbon atoms, and more preferably an average of from about 10 to about 16 carbon atoms. Generally, 2 to 4 carbons is preferred if a high cloud point composition is desired, 6 to 10 carbons is preferred to optimize defoaming efficacy, and 12 to 22 carbons is desired to optimize rinsing efficacy. Various 1,2-epoxyalkane compounds are commercially available from Atochem North America Inc., Philadelphia, PA under the product names VIKALOX 11-14, VIKALOX 12, VIKALOX 16 and others.

The novel surfactant compositions of the present invention provide improved surface treatment of the tableware by the rinse water and subsequently reduces spotting and filming. These epoxy-capped poly(oxyalkylated) alcohols can be formulated in powder and liquid detergent products for automatic dishwashers or in hard surface cleaning products, such as bathroom tile, using methods commercially practised in the detergent industry. These formulations can include, for example, detergent builders, chelating agents, bleaches, anti-wear agents, and combinations thereof, among others.

Suitable detergent builders include inorganic builders such as sodium tripolyphosphate (STPP),

15

20

25

30

35

sodium carbonate, zeolites and mixtures thereof. Where STPP is the detergent builder, the STPP may be employed in the compositions in a range of about 8 to 35 wt. %, preferably about 20 to 30 wt %, and should preferably be free of heavy metal which tends to decompose or inactivate the preferred sodium hypochlorite and other chlorine bleach compounds. The STPP may be anhydrous or hydrated, including the stable hexahydrate with a degree of hydration of 6 corresponding to about 18% by weight of water or more.

Organic builders can also be used including nitrilotriacetic acid and alkali metal salts of tartaric or citric acid.

Where used, a chelating agent can be any one of a wide range of organic or inorganic sequestering agents, examples including phosphoric acid, amino polycarboxylic acids such as EDTA, NTA and DETPA, and polycarboxylic acids such as lactic acid, citric acid, tartaric acid, gluconic acid, glucoheptonic acid, mucic acid, galactonic acid, saccharic acid, fumaric acid, succinic acid, glutaric acid, adipic acid and their alkali metal or ammonium salts. Citric or tartaric acid are preferred chelating acids. The chelating agent if included is present in an amount of up to about 30% and normally lies in the range from about 5% to about 20% by weight. Highly preferred compositions use from about 5% to about 10% by weight of chelating agent in order to minimize any attack by the chelating agent on the glass.

When a bleach is a component in the formulation, the bleach may be an organic chlorine containing bleach, for example, trichloroisocyanuric acid, dichloroisocyanuric acid or a salt of

15

20

25

dichloroisocyanuric acid. Preferably a sodium or potassium salt such as trichloroisocyanuric acid and is employed in an amount of, f r example, 1 t 5% and more preferably 2 to 3% by weight in the cleaning composition. Inorganic bleaching compounds such as chlorinated trisodium polyphosphate (TSPP) or lithium hypochlorite may also be used.

The dishwasher formulations may also include anti-wear or anti-corrosion agents such as an alkali metal silicate, preferably sodium silicate, and may be present in a ratio of 0.1 to 3 and preferably 0.2 to 1 mole per mole of alkali in the cleaning composition.

Alkalinity may be provided by an alkali metal compound, for example, sodium or potassium hydroxide and/or carbonate.

Further suitable conventional ingredients for inclusion in the compositions are hydrotropic agents such as xylene sulfonates, alcohols, perfumes and coloring agents.

while the invention has been described above with reference to specific embodiments thereof, it is apparent that many changes, modifications and variations can be made without departing from the inventive concept disclosed herein. Accordingly, it is intended to embrace all such changes, modifications and variations that fall within the spirit and broad scope of the appended claims.

The following examples are provided to further
illustrate the invention. All parts and percentages
are by weight unless otherwise specified.

EXAMPLE 1

To a 1000 ml round bottom 3-necked flask fitted with a thermometer, on which is placed a thermowatch sensor, a magnetic stirring bar, an equilibrated dropping funnel fitted with a nitrogen inlet, a 5 dry-ice/acetone condenser, and a nitrogen outlet, was added 100 grams (0.6827 moles) of Alfol-610 (Vista Chemical) and 0.4 grams (0.007 moles) of KOH. The alcohol is stirred and heated to 140°C for 1.5 hours. At the end of this time 39.60 grams (0.6827 10 moles) of propylene oxide was added dropwise over The reaction was complete when refluxing one hour. ceased in the dry-ice/acetone condenser. mixture was post reacted for 1.5 hours at 140°C. Ethylene oxide, 450.58 grams (10.24 moles) was then 15 added slowly over 6-8 hours under slow reflux. reaction mixture was then post-reacted for 1.5 hours at 140°C. At the end of this time 151.1 grams (0.629 moles) of 1,2-epoxyhexadecane (Atochem) was added through the dropping funnel. The addition 20 took place over a period of less than 10 minutes. The reaction mixture was post-reacted at 160 ± 3°C for 4.5 hours. At the end of this time the solid product was cooled and removed from the flask. cloud point of a one percent solution of the product 25 in water was <1°C. The hydroxyl number was 56.2 and the primary hydroxyl content was 18.3%.

EXAMPLE 2

To the identical apparatus used in Example 1
30 was added 100 grams (0.6827 moles) of Alfol-610
(Vista Chemical) and 0.4 grams (0.007 moles) of KOH.
The alcohol was stirred and heated to 140°C for 1.5

hours. At the end of this time 39.60 grams (0.6827 moles) of propylene oxide was add d dropwise over one hour. When refluxing ceased in the dry-ice/acetone condenser the reaction was complete. The mixture was post reacted for 1.5 hours at 140°C. Ethylene oxide, 600.78 grams (13.654 moles) was then added slowly over 6-8 hours under slow reflux. reaction mixture was then post-reacted for 1.5 hours at 140°C. To the reaction mixture 116.2 grams (0.480 moles) of 1,2- epoxyhexadecane (Atochem) was 10 added through the dropping funnel in less than 10 minutes. The reaction mixture was post-reacted at 160 ± 3°C for 4.5 hours. At the end of this time the solid product was cooled and removed from the flask. The cloud point of a one percent solution of 15 the product in water was 8°C. The hydroxyl number was 48.7 and the % primary hydroxyl was 19.7.

EXAMPLE 3

Using the identical apparatus of Examples 1 and 2, 100 grams (0.6827 moles) of Alfol-610 (Vista 20 Chemical) and 0.4 grams (0.007 moles) of KOH were added to the flask. The alcohol was stirred and heated to 140°C for 1.5 hours. At the end of this time 39.60 grams (0.6827 moles) of propylene oxide was added dropwise over one hour. The reaction was 25 completed when refluxing ceased in the dry-ice/acetone condenser. The mixture was post , reacted for 1.5 hours at 140°C. Ethylene oxide, 600.78 grams (13.654 moles) was then added slowly over 6-8 hours under slow reflux. The reaction 3.0 mixture was then post- reacted for 1.5 hours at 140°C. Next 74.88 grams (0.480 moles) of 1,2-epoxydecane (Atochem) was added through the

15

20

25

30

dropping funnel in a period of less than 10 minutes. The reaction mixture was post-reacted at 160 ± 3 °C for 4.5 hours. At the end of this time the s lid product was cooled and removed from the flask. The cloud point of a one percent solution of the product in water was 14 °C. The hydroxyl number was 53.0 and the primary hydroxyl content was 25.6%.

EXAMPLES 4-6 AND COMPARATIVE EXAMPLES A, B and C

Loads of tableware including ten 9 inch dinner plates, 10 soda glasses, and assorted tableware were subjected to 5 washing cycles in a Hobart Superba model dishwasher. The washing cycles comprised one wash cycle and two rinses. The maximum temperature during the wash cycle is approximately 137°F and the tableware washing is completed in 70 minutes.

The tableware were washed with each of the products of Examples 1, 2 and 3. In addition, the tableware was washed under identical conditions with a commercial surfactant, Cascade (Procter & Gamble Co.). As additional comparisons, the formulation of Comparison B was tested under identical conditions utilizing the surfactant of Example 8 of U.S. Patent 3,956,401, and Comparison C utilized the surfactant of Example 7b of U.S. Patent 4,925,587. For each washing cycle 20 grams of detergent, including 0.6 grams of surfactant, were used. After each washing, the glassware was evaluated for spotting, streaking and filming using a scale of 1 to 5 in which 1 shows no spots, streaks or film, and 5 indicates the glasses were completely covered with spots, streaks and film. This testing procedure closely follows the Chemical Specialties Manufacturing Association

(CSMA) Test procedure DCC 05A. The results are given in Table I below.

TABLE I

Glassware Rinsing In Automatic Dishwasher

5	Example No.	Spotting	Streaking Filming	
	4. Product of Example 1	2.5	1.0	1.7
	5. Product of Example 2	2.1	1.0	2.1
	6. Product of Example 3	1.4	1.0	3.1
	Comp. A, Cascade	3.5	1.0	3.3
10	Comp. B, Example of U.S. Patent 3,956,401	3.5	1.0	3.4
	Comp. C, Example 7b of U.S.Patent 4,925,587	4.7	1.0	3.9

Glassware cleaned using the products of the invention clearly show a significant improvement in spotting and filming over the commercial detergents. The spotting data is shown graphically in Figure 1.

EXAMPLE 7 AND COMPARATIVE EXAMPLES D AND E

An Automatic Dishwashing Foam Test (CSMA

DCC-01) was used to evaluate products of this invention. Also tested were a commercial product,

"Cascade" (a trademarked commercial product of Procter & Gamble) and the product of Example 7b of U.S. Patent No. 4,925,587. Milk and egg soils were employed in these tests. Measurements were made of the ratio of the revolutions of the dishwasher rotor with detergent and soil as a percentage of the revolutions with water alone. The higher the ratio, the more efficient is the detergent. From the

results provided in Table 2 hereinbelow, it is readily apparent that the product of this invention compares very favorably with the comparative example products. Results are shown in Table 2.

TABLE 2

Defoaming Studies in Automatic Dishwasher

	Example #	Milk Soil	Egg Soil
		ક	ક
	7. Product of Example 3	99	98
10	Comp D., Cascade	91	94
	Comp E., Example 7b of U.S. Patent No. 4,925,587	100	67
	Facenc No. 4,323,367		

WHAT IS CLAIMED IS:

1. An Epoxy-capped poly(oxyalkylated) alcohol characterized by the formula:

 $R_1O[CH_2CH(CH_3)O]_x(CH_2CH_2O)_y[CH_2CH(OH)R_2]_x$

- wherein R₁ is a linear, aliphatic hydrocarbon radical having an average of from about 4 to about 18 carbon atoms including mixtures thereof; and R₂ is a linear, aliphatic hydrocarbon radical having an average of from about 2 to about 26 carbon atoms, or a mixture thereof; x is an integer having a value from 1 to about 3; y is an integer having a value from 5 to about 30; and z is an integer having a value of from 1 to about 3.
- 2. The epoxy-capped poly(oxyalkylated) alcohol of claim 1 characterized in that z is from 1 to about 2.
 - 3. The epoxy-capped poly(oxyalkylated) alcohol of claim 1 characterized in that R_2 has an average of from about 2 to about 14 carbon atoms.
- 20 4. The epoxy-capped poly(oxyalkylated) alcohol of claim 1 characterized in that x is from 1 to about 2.
- 5. The epoxy-capped poly(oxyalkylated) alcohol of claim 1 characterized in that y is from about 10 to about 25.
 - 6. The epoxy-capped poly(oxyalkylated) alcohol of claim 1 characterized in that R_1 has an average of from about 4 to about 12 carbon atoms.

- 7. The epoxy-capped poly(oxyalkylated) alcohol of claim 4 characterized in that x is 1.
- 8. The epoxy-capped poly(oxyalkylated) alcohol of claim 7 characterized in that z is 1.
- 9. The epoxy-capped poly(oxyalkylated) alcohol of claim 8 characterized in that R₂ has an average of from about 2 to about 14 carbon atoms.
 - 10. The epoxy-capped poly(oxyalkylated) alcohol of claim 9 characterized in that y is from about 10 to about 20.
 - 11. The epoxy-capped poly(oxyalkylated) alcohol of claim 10 characterized in that $R_{\rm i}$ has an average of from about 4 to about 12 carbon atoms.

10

15

12. An automatic dishwasher compositi n characterized by containing an epoxy-capped poly(oxyalkylated) alcohol represented by the formula:

 $R_1O[CH_2CH(CH_3)O]_x(CH_2CH_2O)_y[CH_2CH(OH)R_2]_z$

wherein R₁ is a linear, aliphatic hydrocarbon radical having an average of from about 4 to about 18 carbon atoms including mixtures thereof; and R₂ is a linear, aliphatic hydrocarbon radical having an average of from about 2 to about 26 carbon atoms including mixtures thereof; x is an integer having a value from 1 to about 3; y is an integer having a value from 5 to about 30; and z is an integer having a value of from 1 to about 3, and at least one component selected from the group consisting of detergent builder, bleach, anti-wear agent, and combinations thereof.

10

15


20

13. A cleaning composition for cleaning hard surfaces characterized by containing an aqueous or organic solvent and an epoxy-capped poly(oxyalkylated) alcohol surfactant represented by the formula:

 $R_1O[CH_2CH(CH_3)O]_x(CH_2CH_2O)_y[CH_2CH(OH)R_2]_x$

wherein R₁ is a linear, aliphatic hydrocarbon radical having an average of from about 4 to about 18 carbon atoms including mixtures thereof; and R₂ is a linear, aliphatic hydrocarbon radical having an average of from about 2 to about 26 carbon atoms including mixtures thereof; x is an integer having a value from 1 to about 3; y is an integer having a value from 5 to about 30; and z is an integer having a value of from 1 to about 3.

- 14. A method for cleaning soiled tableware which comprises contacting the soiled tableware in a dishwashing machine in an aqueous wash bath characterized by having dispersed therein an effective amount of the composition of claim 12 to obtain clean tableware having substantially reduced films and spots.
- 15. A method for cleaning hard surfaces which is characterized by contacting the hard surfaces
 25 with an effective amount of the composition of claim
 13 to obtain said cleaning of said hard surfaces.



INTERNATIONAL SEARCH REPORT

International application No. PCT/US94/02884

	A. CLASSIFICATION OF SUBJECT MATTER				
IPC(5)	:C07C 43/11,43/18,43/20; C11D 1/72, 3/075, 3/20		ţ		
US CL	:252/174.19, 174.21, 174.22; 568/606,618,622,625 o International Patent Classification (IPC) or to both	national classification and IPC	1		
		inational organization and to	 i		
	LDS SEARCHED				
Minimum d	ocumentation searched (classification system followed	by classification symbols)			
U.S. :	252/174.19, 174.21, 174.22; 568/606,618,622,625; 1	34/25.2			
Documentat	tion searched other than minimum documentation to the	extent that such documents are included	in the fields searched		
Electronic d	data base consulted during the international search (na	me of data base and, where practicable,	search terms used)		
A.C.S. I	FILE -REGISTRY		İ		
C POC	NUMBER CONCIDERED TO BE DELEVANT				
C. DOC	CUMENTS CONSIDERED TO BE RELEVANT				
Category*	Citation of document, with indication, where an	propriate, of the relevant passages	Relevant to claim No.		
x	US.A. 4,827,028 (Scardera et a	al.) 02 May 1989, note	1-11		
	column 2, formulas (A) and (B)				
	50.6 2 , 10 3 3 3 3				
Y,P	US,A, 5,294,365 (Welch et al.	15 March 1994, note	12-15		
' <i>'</i> '	column 3, lines 26-28 and 54-64.	, , , , , , , , , , , , , , , , , , , ,			
	Column 5, lines 20-20 and 54-04.		_		
\ \	110 A 4 000 001 (Dougle of all)	06 February 1990 - 50to	12-15		
Υ	US,A, 4,898,621 (Pruehs et al.)		12-19		
	column 5, line 51 to col. 6, line 1	/·	:		
Α	US,A, 4,317,940 (Scardera et al.)	02 March 1982	1-15		
		·			
Α	US,A, 3,956,401 (Scardera et al.)	11 May 1976	1-15		
Α	US,A, 4,925,587 (Schenker et al.) 15 May 1990	1-15		
		•			
	<u> </u>				
Furth	her documents are listed in the continuation of Box C	See patent family annex.			
• Sp	ecial entegories of cited documents:	"T" inter document published after the inter	ernational filing date or priority		
	current defining the general state of the art which is not considered	date and not in conflict with the applic principle or theory underlying the inv			
	be of particular relevance	"X" document of particular relevance; th	e claimed invention cannot be		
	rlier document published on or after the international filing date	considered novel or cannot be conside when the document is taken alone	ered to involve an inventive step		
cit	cument which may throw doubts on priority claim(s) or which is ed to establish the publication date of another citation or other	"Y" document of particular relevance; th	e chimed invention cannot be		
	ecial reason (as specified)	considered to involve an inventive	step when the document is		
	cument referring to an oral disclosure, use, exhibition or other ears	combined with one or more other suc being obvious to a person skilled in t			
°P° do	current published prior to the international filing date but later than	"&" document member of the same patent	l family		
	priority date claimed	In			
Date of the	actual completion of the international search	Date of mailing of the international se	aren report		
JUL 1 9 1994					
20 JUNE 1774					
Name and mailing address of the ISA/US Authorized of the ISA/US					
Commissioner of Palents and Trademarks Box PCT PAUL E. KONOPKA					
Washington, D.C. 20231					
Facsimile N	lo. (703) 305-3230	Telephone No. (703) 308-3810			